

American Wire and Cable

Phone 440 235-1140 Fax 440 235-3330

UL Style	CSA	AWG	STND**	MIL	TEMP	Voltage	Nominal OD
Glass Braided Silicone Rubber Fixture Wire - 200 C							
SF1	SEW-1	16	7/ST	15 Mil	200	300	0.103
SF1	SEW-1	18	7/ST	15 Mil	200	300	0.093
3075	SEW-2	10	19/ST	45 Mil	200	600	0.218
3074	SEW-2	12	19/ST	30 Mil	200	600	0.164
SF2, 3071	SEW-2	14	7/ST	30 Mil	200	600	0.147
SF2, 3071	SEW-2	16	7/ST	30 Mil	200	600	0.133
SF2, 3071	SEW-2	18	7/ST	30 Mil	200	600	0.115
Glass Braided Silicone Rubber Fixture Wire - 150 C							
SFF2, 3070, SRML	SEWF-2	12	65/30	30 Mil	150	600	0.164
SFF2, 3070, SRML	SEWF-2	14	41/30	30 Mil	150	600	0.147
SFF2, 3070, SRML	SEWF-2	16	26/30	30 Mil	150	600	0.133
SFF2, 3070, SRML	SEWF-2	18	16/30	30 Mil	150	600	0.115
SFF2, 3101, SRML		10	105/30	45 Mill	150	600	0.218
Put-ups: Reels or Plastic Spools							
** Other possible stranding: Solid - All stranding is Tinned							

#####