

American Wire and Cable

Phone 440 235-1140 Fax 440 235-3330

UL Style	AWG	Stranding	Dimensions	TEMP	Voltage
SPT MULTICONDUCTOR					
SPT-2	18/2	16/30	NA	105C	300V
SPT-2	18/3	16/30	.335x.140	105C	300V
SPT-3	14/2	41/30	NA	105C	300V
SPT-3	14/3	41/30	.510x.235	105C	300V
SPT-3	16/2	26/30	NA	105C	300V
SPT-3	16/3	26/30	.425x.190	105C	300V
SPT-3	18/2	16/30	.325x.174	105C	300V
SPT-3	18/3	26/30	.388x.173	105C	300V
AWM MULTICONDUCTOR					
2082/ 2298	14/2	41/30	.462x.230	105C	300V
2081/ 2297	16/3	26/30	.470x.185	105C	300V
2081/ 2297	18/3	16/30	.432x.176	105C	300V
2080/ 2296	16/2	26/30	.330x.185	105C	300V
2080/ 2296	18/2	16/30	.302x.176	105C	300V
RV MULTICONDUCTOR					
RV	16/2	26/30	.243x.117	105C	600V
RV	14/2	41/30	.275x.135	105C	600V
RV	12/2	65/30	.310x.153	105C	600V

4/5/2013